



**MODEL NUMBER:** S-7213-LG Sadie Locking Glider

**DIMENSIONS** w29.5 d31 h41.5  
ah 23.5 sh 18.5 sd 17.5 iw 21.5

**SEAT CUSHION:** Loose Seat- reversible seat cushion with nylon zipper closure. Air -vents are used in the back border of the cushion when non-breathable fabric have been selected. Standard with moisture barrier decking.

H3L cushions are constructed using the latest in soy-based chemical technology. Soy-based cushions are sustainable, and renewable. H3L Poly is a 2.5 density, 30 IFD Ultracel HR foam.

**SEAT SUPPORT:** 8.5 gauge "No Sag" sinuous spring attached with "No-Sag" squeak-proof clips. Flat spring construction creates little or no crown to the seat surface, preferred for Senior Living.

**BACK CUSHION:** Tight Back

Tight back cushions are constructed using the latest in soy-based chemical technology. Soy-based cushions are sustainable, and renewable. Depending on the design and style the back cushions range from 1.0-1.5 pound per cubic foot density polyurethane with a 17-35 IFD (Indentation Force Deflection), with a .75 oz. Dacron topper. All Fairfield foam cushions meets CAL 117-2013.

**BACK SUPPORT:** 4" nylon webbing covered with heavy duty FLW propex and Insul Pad to give proper shape and support.

**FRAME:** Solid kiln dried hardwoods and engineered laminated hardwood veneers. Solids are harvested from certified sustainable U.S. forest. Plywood is compliant with California A Resource Board (CAEB) 93120 phase 2, formaldehyde emissions requirements of the Airborne Toxic Control Measure ( ATCM).

**FRAME DESCRIPTION:** Frames are handcrafted using the most trusted construction techniques that have been in practice for centuries. To insure frame integrity and compatibility with style and design requirements, frames are engineered to use a variety of joint construction. Triple dowel construction is standard. Many major stress joints feature both triple doweling, mortise and tenon and corner blocks that are attached with PVAC glue, staples and four screws. Frames are federally tested to perform at a minimum of 300 pound weight capacity.

**GLIDES:** N/A

**FINISH:** Fairfield Standard lacquer finish is a 9 step pre-catalyzed, nitrocellulose process. The "pre-cat" finish has UV inhibitors to reduce harmful effects of the sunlight and features silver ion technology for antimicrobial protections. Silver ions inhibits the growth of mold, mildew, fungus and bacteria on the finish surface. Fair-Shield Plus is a 7 step conversion varnish that offers enhanced chemical, moisture, mar and scratch resistance over a "pre-cat" system. It is ideal for high-use commercial environments. Fair-Shield Plus contains a clear top-coat conversion varnish that forms a chemically cross-linked barrier that is more resistant to wear and abrasion and is more impervious to moisture and commercial cleaning material. It is also formulated with UV inhibitors and features silver ion technology. There is no up-charge for Fair-Shield Plus finish.

**UPHOLSTERY:** Multi-fabric combinations and contrast welting available. Nails head trim optional on the sides and top of out back.

**WARRANTY:** Fairfield warrants its merchandise to be free of defects in materials and workmanship for Five (5) years under normal single shift use and conditions to the original purchaser. See the price list for exceptions. Textiles are covered under separate warranty by the textile supplier.